SHIELD THERMAL BLANKET

CAMP SUPPORT

DESCRIPTION

The Blanket has a 2 fold fleece layer and is knitted dry raised on both sides. There is an additional insulating polyfill layer for increased thermal performance.

The Blanket has a seam finish of 10 to 13 stitches per 10 cm. The resistance to airflow is less than 1000 L/m² /s as per ISO 9237 under a 100 Pa pressure drop. Organoleptic tests confirm there is no bad odor, no irritation, no dust, a PH between 4 and 9, and the product is fit for human use and free from harmful VOC's.

After washing there is less than 5% loss in tensile strength as per ISO 6330 and 13934-1, shrinkage and weight loss as per ISO 6330.

PERFORMANCE

DIMENSIONS	150 x 200 cm ± 1%	**TOG**	>0,4 RCT
WEIGHT	Min. 500 g - max. 1000 gsm	**FLAME RESISTANCE**	As per ISO 12952-3&4
TENSILE STRENGTH	>250 N warp and weft as per ISO 13934-1	**CIGARETTE RESISTANCE**	As per ISO 12952-1&2
THICKNESS	>9,5mm as per ISO 5084		

SHIELD BY ALPINTER
info@shieldtents.com
www.shieldtents.com
VAT BE 0435 022 630
+32 55 23 17 54
Rue Charles de Gaulle 7, 9600 Renaix, Belgium
Brand from WOT

COLOUR AND MATERIALS

COLOUR	MATERIAL	FILLING
Grey	Polyester as per ISO 1833	100% polyester polyfill

PACKAGING AND SHIPPING

A Thermal Blanket comes in a bale of 15 pieces.

CONTENTS
15x Blankets

1 BALE
Weight: Approx. 26 kg
Volume/Dimensions: Upon request